MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH ZIEGELTALSTRASSE 2 D-93346 IHRLERSTEIN TELEFON 09441-176940 TELEFAX 09441-1769499 www.moellerstonecare.eu info@moellerstonecare.eu



MOELLER STONE CARE

CERAMIC TILES - BRICK TILES TI-6

unglazed –

Care instruction tested

CONDITIONS

When treating a newly laid surface ensure sufficient drying time for the moisture to escape from the surface and substructure (maximum 2-4% residual moisture content).

Allow 2-3 weeks drying time for an adhesive bed and 4-6 weeks for mortar bed.

Drying times are indicative only and are subject to variation depending on the weather and the object and can be longer.

It's essential that any under-floor heating has been switched off and the surface is at a normal temperature, adequately cleaned, free of stains, dry and absorbent.

Always test in an inconspicuous place to determine suitability and coverage. Always read the labels carefully. Ensure the area around the surface to be treated is well ventilated.

HELP FOR GROUTING

Before grouting: S45 Joint Protector -water based- Coverage: approx. 10-15 m²/litre

CLEANING

Construction dirt:R57Ceramic Tile Intensive CleanerCoverage:approx.10-80 m²/litreCement smears:R63Cement Film RemoverCoverage:approx.5-50 m²/litreEfflorescence:R65Terracotta CleanerCoverage:approx.10-40 m²/litre

Stains: Refer to Technical Information Sheet No. 1

After cleaning the surface must be allowed to dry for at least 1 to 2 days to a residual moisture content of 2-4% before any further treatment can take place.

PROTECTION – inside and outside

Without enhancing colour:S32WStain Protection -water based-Coverage: approx.5-20 m²/litreMinimal colour enhancing:S34NStain Protection -extra-Coverage: approx.5-20 m²/litreStrong colour enhancing:S44Colour Enhancer -extra-Coverage: approx.5-20 m²/litre

Once dry the residual material is not harmful to health. Therefore impregnators can be used on kitchen tops.

MAINTENANCE - inside and outside

Regular maintenance: P24 Liquid Stone Soap -no rinse- (natural product)

add approx. 25-50 ml for every 10 liters of wash water

Strong loaded surfaces: P26 Terracotta Card

-only for inside- add approx. 100-200 ml for every 10 liters of wash water,

that means five times using P24, than one time using P26.

Periodical intensive cleaning: R57 Ceramic Tile Intensive Cleaner

periodical if necessary do a cleaning with soft brush

OLD SURFACES

Films of maintenance

products and dirt:

R57 Ceramic Tile Intensive Cleaner

Coverage: approx. 10-80 m²/litre

Layer of Waxes:

R54 Stripper - Stain Remover

Coverage: approx. 5-10 m²/litre

For optimum results and durability of further applications, older surfaces should be thoroughly cleaned. Repeat cleaning if necessary. After necessary drying time is allowed, proceed with products indicated under "PROTECTION". Always follow individual product directions.

ENVIRONMENT

All specialist products comply with the German Detergent Act and are registered with the Federal Environmental Offices in Berlin.

Our specialized products have been recommended for decades by leading ceramic tiles producers.

This technical instruction card is for advice only and is supplied without obligation. We require that the person making the application adapts all data concerning the application of the products to local conditions and the materials to be cleaned. We reserve the right to make changes to our products without warning as a result of technological advancement. The person conducting the application is responsible for any third person liabilities and ensuring compliance with any local laws or regulations.

All products are available from many reputable natural stone and tile dealers.

Your local dealer: