



## GRANITE – GNEISS

– quarry rough – flamed – bush hammered –

– rough brushed – blasted – rough honed –

Care instruction tested to DIN 18332 (EN 12440)

## CONDITIONS

When treating a newly laid surface ensure sufficient drying time for the moisture to escape from the surface and substructure (maximum 2-4% residual moisture content).

Allow 2-3 weeks drying time for an adhesive bed and 4-6 weeks for mortar bed.

Drying times are indicative only and are subject to variation depending on the weather and the object and can be longer.

**MOELLER** STONE CARE

It's essential that any under-floor heating has been switched off and the surface is at a normal temperature, adequately cleaned, free of stains, dry and absorbent.

Always test in an inconspicuous place to determine suitability and coverage. Always read the labels carefully. Ensure the area around the surface to be treated is well ventilated.

HELP FOR GROUTING							
Before grouting:	S45	Joint Protector -water based-	Coverage:	approx.	10-15 m <sup>2</sup> /litre		
CLEANING							
Construction dirt:	R55	Intensive Cleaner -acid free-	Coverage:	approx.	10-30 m <sup>2</sup> /litre		
Cement smears:	R75	Exterior Stone Cleaner -acid based-	Coverage:	approx.	10-50 m <sup>2</sup> /litre		
Stains:	Refer t	please test if surface is acid resistance o Technical Information Sheet No. 1					
After cleaning the surface must be allowed to dry for at least 1 to 2 days to a residual moisture content of 2-4% before any further treatment can take place.							
PROTECTION							
Without enhancing colour:	S32W	Stain Protection -water based- (inside and outside)	Coverage:	approx.	5-20 m <sup>2</sup> /litre		
Minimal colour enhancing:	S34N	Stain Protection -extra- (inside and outside)	Coverage:	approx.	5-20 m <sup>2</sup> /litre		
Strong colour enhancing:	S44	Colour Enhancer -extra- (inside and outside)	Coverage:	approx.	5-20 m <sup>2</sup> /litre		
Colour enhancing matte finish:	<b>S</b> 35	Stone Sealer -matte finish- (only for inside)	Coverage:	approx.	5-10 m <sup>2</sup> /litre		
Colour enhancing satin finish:	S37	Stone Sealer -satin finish- (only for inside)	Coverage:	approx.	5-10 m <sup>2</sup> /litre		
Once dry the residual material is not harmful to health. Therefore impregnators can be used on kitchen tops.							
MAINTENANCE – inside and outside							
Regular maintenance:	P24	Liquid Stone Soap -no rinse- (natural product) add approx. 25-50 ml for every 10 liters of wash water					
Strong loaded surfaces:	P23	Polish-Preserver -no rinse-					
-only for inside-		add approx. 100-200 ml for every 10 liters of wash water, that means five times using P24, than one time using P2					
Periodical intensive cleaning:	R55	Intensive Cleaner -acid free- periodical if necessary do a cleaning with soft brush					
OLD SURFACES							
Films of maintenance							
products and dirt:	R55	Intensive Cleaner -acid free-	Coverage:	approx.	10-30 m <sup>2</sup> /litre		
Layer of Waxes:	R54	Stripper - Stain Remover	Coverage:	approx.	5-10 m <sup>2</sup> /litre		
For optimum results and durability of further applications, older surfaces should be thoroughly cleaned. Repeat cleaning if necessary. After necessary drying time is allowed, proceed with products indicated under "PROTECTION". Always follow individual product directions.							

## **ENVIRONMENT**

All specialist products comply with the German Detergent Act and are registered with the Federal Environmental Offices in Berlin.

Our specialized products have been recommended for decades by leading natural stone producers.

This technical instruction card is for advice only and is supplied without obligation. We require that the person making the application adapts all data concerning the application of the products to local conditions and the materials to be cleaned. We reserve the right to make changes to our products without warning as a result of technological advancement. The person conducting the application is responsible for any third person liabilities and ensuring compliance with any local laws or regulations.

## All products are available from many reputable natural stone and tile dealers.

d person liabilities and ensuing compliance with any local laws of regulations.	
Your local dealer:	