MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH ZIEGELTALSTRASSE 2 D-93346 IHRLERSTEIN TELEFON 09441-176940 TELEFAX 09441-1769499 www.moellerstonecare.eu info@moellerstonecare.eu



MOELLER STONE CARE

COMPOSITE-QUARTZ Floors

TI-18

- cleaning and maintenance -

Care instruction tested

CONDITIONS

When treating a newly laid surface ensure sufficient drying time for the moisture to escape from the surface and substructure (maximum 2-4% residual moisture content).

Allow 2-3 weeks drying time for an adhesive bed and 4-6 weeks for mortar bed.

Drying times are indicative only and are subject to variation depending on the weather and the object and can be longer.

It's essential that any under-floor heating has been switched off and the surface is at a normal temperature, adequately cleaned, free of stains, dry and absorbent.

Always test in an inconspicuous place to determine suitability and coverage. Always read the labels carefully. Ensure the area around the surface to be treated is well ventilated.

CLEANING

Construction dirt:R85Composite Quartz Intensive CleanerCoverage: approx. 20-60 m²/litreCement smears:R63Cement Film RemoverCoverage: approx. 5-50 m²/litre

Stains: Refer to Technical Information Sheet No. 1

After cleaning the surface must be allowed to dry for at least 1 to 2 days to a residual moisture content of 2-4% before any further treatment can take place.

PROTECTION – inside and outside

Without enhancing colour: S46W Composite Quartz Stain Protection -water based- Coverage: approx. 20-40 m²/litre

Minimal colour enhancing: S46 Composite Quartz Stain Protection Coverage: approx. 20-40 m²/litre

Once dry the residual material is not harmful to health.

MAINTENANCE - inside and outside

Regular maintenance: P11 Composite-Quartz Care Cleaner

add approx. 25 ml for every 10 liters of wash water

Periodical intensive cleaning: R85 Composite Quartz Intensive Cleaner

periodical if necessary do a cleaning with soft brush

OLD SURFACES

Films of maintenance

products and dirt:R85Composite Quartz Intensive CleanerCoverage:approx.20-60 m²/litreLayer of Waxes:R54Stripper - Stain RemoverCoverage:approx.5-10 m²/litre

For optimum results and durability of further applications, older surfaces should be thoroughly cleaned. Repeat cleaning if necessary. After necessary drying time is allowed, proceed with products indicated under "PROTECTION". Always follow individual product directions.

ENVIRONMENT

All specialist products comply with the German Detergent Act and are registered with the Federal Environmental Offices in Berlin.

Our specialized products have been recommended for decades by leading composite quartz tiles producers.

This technical instruction card is for advice only and is supplied without obligation. We require that the person making the application adapts all data concerning the application of the products to local conditions and the materials to be cleaned. We reserve the right to make changes to our products without warning as a result of technological advancement. The person conducting the application is responsible for any third person liabilities and ensuring compliance with any local laws or regulations.

All products are available from many reputable natural stone and tile dealers.

Your local dealer: